

## MATERIAL SAFETY DATA SHEET

## SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) Ever-Wear Air Tool Treatment (ET 130)	DATE 10/15/2008
MANUFACTURER'S NAME QMI	EMERGENCY TELEPHONE #: QMI: (800) 255-8138 CHEM-TEL: (800) 255-3924
ADDRESS (Number, Street, City, State and Zip Code) 3606 Craftsman Blvd., Lakeland, FL 33803 USA	
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. None	
ADDITIONAL HAZARD CLASSES (as applicable) In accordance with OSHA 29 CFR 1910-1200.	
CHEMICAL FAMILY Petroleum	FORMULA Proprietary

SECTION II  
(list ingredients)

CAS REGISTRY NO.	%W	%V	CHEMICAL NAME(S)	LISTED AS A CARCINOGEN
64741-88-4	85		Paraffinic Base Oil	Not Listed
			Aliphatic and Aromatic Solvents	Not Listed
9002-84-0	>1		Poly Tetra Fluoroethylene	Not Listed
Proprietary			Non-Toxic Surfactant and Phosphate Radical	

## SECTION III - PHYSICAL DATA

BOILING POINT 520°F 271°C	SPECIFIC GRAVITY 0.91	
VAPOR DENSITY (AIR=1) 1>	EVAPORATION RATE <1	PERCENT SOLD BY WEIGHT (%) 2.00%
SOLUBILITY IN WATER Insoluble		
APPEARANCE AND ODOR Dark Liquid, Mild Petroleum Odor	IS MATERIAL:	<u>LIQUID</u> SOLID GAS PASTE POWDER

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT 360°F 174°C	METHOD USED Open Cup	FLAMMABLE LIMITS	LEL N/A	UEL N/A
EXTINGUISHING MEDIA CO2 Foam if needed or water fog.				
SPECIAL FIRE FIGHTING PROCEDURES None				
UNUSUAL FIRE AND EXPLOSION HAZARDS Water may cause frothing				

### SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - Conditions to Avoid Slight eye and skin irritation can result.	THRESHOLD LIMIT VALUE PERMISSIBLE EXPOSURE LIMIT 5.00 mg/m <sup>3</sup> OTHER LIMIT: OSHA PeL 5 mg/m <sup>3</sup>
PRIMARY ROUTES OF ENTRY 4 INHALATION 4 SKIN CONTACT 4 OTHER (Specify) _____	
EMERGENCY AND FIRST AID PROCEDURES Skin: Wash areas with water Eyes: Flush with water. If Swallowed: Do not induce vomiting	

### SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Strong oxidizers and extreme heat
INCOMPATIBILITY (materials to avoid) Strong oxidizers			
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID:
	WILL NOT OCCUR	X	Extreme Heat

### SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Mop or absorb on fire retardant treated sawdust or other absorbent material.
WASTE DISPOSAL METHOD Dispose into regulatory disposal facilities in accordance with local laws.

### SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION None other than adequate ventilation.		
VENTILATION	Local Exhaust (Specify Rate)	SPECIAL: None
	ADEQUATE	OTHER: None
PROTECTIVE GLOVES (Specify type) Oil impervious	EYE PROTECTION (specify type) Normal industrial protection	
OTHER PROTECTIVE EQUIPMENT None required.		

### SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING No special precautions required.
---

#### ADDITIONAL HEALTH DATA COMMENT

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

