



MATERIAL SAFETY DATA SHEET

SECTION I – Identification of the Product and Company

PRODUCT NAME OR NUMBER (as it appears on label) QMI Engine Clean	DATE 03/20/2009
MANUFACTURER'S NAME QMI	EMERGENCY TELEPHONE #: QMI (863) 665-3338 CHEM-TEL: (800) 255-3924
ADDRESS (Number, Street, City, State and Zip Code) 3606 Craftsman Blvd., Lakeland, FL 33803	
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. None OSHA 29 CFR 1910-1200	
ADDITIONAL HAZARD CLASSES (as applicable) None	
CHEMICAL FAMILY Petroleum	FORMULA Proprietary

SECTION II – Composition/Information on Ingredients

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)	R PHRASES
64742-30-9	> 80	Aliphatic Petroleum Distillate	R52
64742-88-7	> 10	Aliphatic Hydrocarbon	R20/21/22/36/37/38/51
Proprietary	> 5	Aliphatic Hydrocarbon	R20/21/22/36/37/38/51

SECTION III – Hazards Identification

Not Classified

SECTION IV – First Aid Measures

INGESTION: Rinse mouth with water. Call physician.
SKIN CONTACT: Wash thoroughly with soap and water.
EYE CONTACT: Wash with copious quantities of water.
INHALATION: Clear air passage, get person to fresh air.

SECTION V – Fire-Fighting Measures

EXTINGUISHING MEDIA: Use foam or carbon dioxide dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Use supplied-air breathing equipment for enclosed or confined spaces

SECTION VI – Accidental Release Measures

IN CASE OF SPILLAGE: Scoop up excess, wipe up with rags or other absorbent materials, pick up residue with diatomaceous earth. Dispose of in accordance with local laws.

SECTION VII – Handling and Storage

Store in cool, dry place- normal precautions as with any petroleum product.

SECTION VIII – Exposure Controls/Personal Protection

RESPIRATORY PROTECTION: None required

VENTILATION: Local exhaust

PROTECTIVE GLOVES: None required

EYE PROTECTION: Goggles

OTHER PRECAUTIONS: Wash hands after use

SECTION IX – Physical and Chemical Properties

APPEARANCE AND ODOR: Clear liquid – petroleum odor.

pH: Neutral

FLASH POINT: (C.O.C.) 240°F – 115°C

SOLUBILITY: Insoluble

INCOMPATIBLE MATERIALS: Strong oxidizing materials

SECTION X – Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Strong oxidizing materials.

SECTION XI – Toxicological Information

ROUTES OF ENTRY/SYMPTOMS OF CONTACT:

INHALATION: Very low risk.

SKIN AND EYES: Very low risk- minor irritation and redness may occur.

INGESTION: May be hazardous if ingested in large quantities.

SECTION XII – Ecological Information

Very low risk to domestic animals- may be harmful to fish and waterfowl if introduced into waterways.

SECTION XIII – Disposal Considerations

Dispose of excess or unused material and containers in accordance with local laws.

SECTION XIV – Transport Information

Not classified as hazardous for transport.

SECTION XV – Regulatory Information

EUROPEAN LABELING;

SAFETY PHRASES:

S 3 KEEP IN A COOL PLACE.

RISK PHRASES

R 20 HARMFUL BY INHALATION.

R 21 HARMFUL IN CONTACT WITH SKIN.

R 22 HARMFUL IF SWALLOWED.

R 36/37/38 IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

R 51 TOXIC TO AQUATIC ORGANISMS.

R 52 HARMFUL TO AQUATIC ORGANISMS.

SYMBOLS

N, T, Xi

All ingredients are listed in EPA-TSCA inventory. The information contained in this data sheet does not constitute the user's own assessment of workplace risk as required by legislation.

SECTION XVI – Other Information

ADDITIONAL HEALTH DATA COMMENT

The above information is based the data of which we are aware and is believed to be correct as of the data hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.